

LOVAG Registered Laboratory 2014

<u>LOVAG CB</u>	<u>Id Code</u>	<u>Name</u>	<u>Address</u>	<u>Observer</u>
IMQ LABORATORY (ITALY)	IQ01	IMQ - Low Voltage Appliances (EG0002)	Via Quintiliano, 43 I-20138 Milano	Gianluca MASTRODOMENICO

LOVAG Scheme Scope

Main Standards in the LOVAG Scheme			
<u>Category</u>	<u>Standards</u>	<u>Description</u>	
<input checked="" type="checkbox"/>	POW	IEC/EN 60947-1	Low-voltage switchgear and controlgear
<input checked="" type="checkbox"/>	POW	IEC/EN 60947-2	Circuit-breakers
<input checked="" type="checkbox"/>	POW	IEC/EN 60947-3	Switches, disconnectors, switch-disconnectors and fuse-combination units
<input type="checkbox"/>	POW	IEC/EN 60947-4-1	Electromechanical contactors and motor starters
<input checked="" type="checkbox"/>	POW	IEC/EN 60947-5-1	Auxiliary Switch
<input checked="" type="checkbox"/>	POW	IEC/EN 60439-1 IEC/EN 61439-1 & IEC/EN 61439-2	Low-voltage switchgear and controlgear assemblies Part 2: Power switchgear and controlgear assemblies
<input checked="" type="checkbox"/>	POW	IEC/EN 61439-1 & IEC/EN 61439-6	Low-voltage switchgear and controlgear assemblies Part 6: Busbar trunking systems (busways)
<input checked="" type="checkbox"/>	INST	IEC/EN 62208-1	Empty enclosures for low voltage switchgear and controlgear assemblies

General Overview of Scope of tests (*)		
<u>Type of tests:</u>	<u>Test description:</u>	<u>Maximum Test limits:</u>
<input checked="" type="checkbox"/> High-current tests	<input checked="" type="checkbox"/> Short-circuit switching capacity <input checked="" type="checkbox"/> AC <input type="checkbox"/> DC <input type="checkbox"/> Overload switching capacity <input checked="" type="checkbox"/> AC <input type="checkbox"/> DC <input checked="" type="checkbox"/> Making/breaking capacity <input checked="" type="checkbox"/> AC <input checked="" type="checkbox"/> DC <input checked="" type="checkbox"/> Short-time withstand current <input checked="" type="checkbox"/> Impulse withstand current <input type="checkbox"/> Arc fault withstand capacity	Voltage : 690 V / Current : 10 kA Voltage : V / Current : kA Voltage : V / Current : A Voltage : V / Current : kA Voltage : 720 V / Current : 600 A Voltage : 250 V / Current : 40 A Current : 15 kA Time : 1 s Current : A Energy : kA ² s
<input checked="" type="checkbox"/> Insulation tests	<input checked="" type="checkbox"/> High voltage <input checked="" type="checkbox"/> Impulse withstand voltage <input checked="" type="checkbox"/> Minimum Leakage current detection	Voltage : 10 kV Voltage : 18 kV Current : 0.5 mA
<input checked="" type="checkbox"/> Temperature-rise tests	<input checked="" type="checkbox"/> AC / <input checked="" type="checkbox"/> DC max. current <input checked="" type="checkbox"/> Minimum Impedance measurement	Current : 500 A / Current : 40 A Ω
<input checked="" type="checkbox"/> Tripping behaviour	<input checked="" type="checkbox"/> AC / <input checked="" type="checkbox"/> DC max. current	Current : 300 A / Current : 40 A
<input checked="" type="checkbox"/> Lifespan	<input checked="" type="checkbox"/> Mechanical lifespan <input checked="" type="checkbox"/> Electrical durability: <input checked="" type="checkbox"/> AC <input checked="" type="checkbox"/> DC	Voltage : 690 V Current : 125 A Voltage : 250 V Current : 40 A
<input type="checkbox"/> Mechanical properties of terminals		
<input type="checkbox"/> EMC tests		
<input type="checkbox"/> Climatic tests		
<input type="checkbox"/> Vibration and shock tests		
<input checked="" type="checkbox"/> Degree of protection tests	<input checked="" type="checkbox"/> IP-code (water and solid bodies) <input checked="" type="checkbox"/> IK-code (impact resistance of enclosures)	IP 68 IK 10

(*) The provided technical information are not contractual and could be different, according to the relevant test specifications of a specific product standard.

For more technical specifications or details, please refer to laboratory documentations or website.